

PT Series Central Storage Unit

Supplies Chilled Water for up to Six Bubblers

The PT30 is ideal for schools, universities and the mining industry where large volumes of cold water are needed at the one time. This unit delivers 90 litres of chilled water per hour and has a tin plated storage tank holding 135 litres fitted with a drain for periodic cleaning. Ideal application is a connection with up to 6 bubblers. A removable lid gives instant access to the refrigeration system.

Contact us for a comprehensive list of parts available for this model.

Specifications	
Product Code	PT30
Max Cooling (L/h)	90
Filtered	No
Type	Central Storage
Connections	3/4" BSP compression fittings
Reservoir	135 L
Refrigeration	R134A
Outlet Temperature	Cold (10°C)
Temperature Control	Factory pre-set
Compressors	1/2 hp nominal capacity, hermetically sealed for silent running
Condenser	Copper tube and expanded aluminium fin
Electrical	240 volts, 50Hz, 3.74 amps
Performance to ARI 1010-94 Standard	Inlet water – 26.7°C, Outlet water – 10°C, Ambient air – 32.2°C
Weight (Packed)	90 kg
Dimensions (mm)	650 L x 720 W x 134 H - Packed
Warranty	1 year - comprehensive coverage, 5 years - compressor replacement.
Notes	<ol style="list-style-type: none"> 1. For installation details specific to your use of the PT30, contact the manufacturer or distributor. 2. Pressure relief valve supplied.

